

WVI00017



Face protection that enables the wearer to work on or be in the vicinity of live electric parts with arc protection up to 26.0 cal/cm² (According to ASTM F2178-12). Recommended for use with balaclava. Securely flips up and down. Works with all Zenith series helmets by attaching directly to the Visor Attachment Slots.

TECHNICAL DETAILS



MATERIAL
Polycarbonate



STANDARD
ASTM F2178-12
ATPV 26.0 cal/cm² HRC 3



OPTICAL CLASS
1



CATEGORY
III



WEIGHT
0.9 lb



ANSI Z87+
Yes

TECHNOLOGIES



> CRI 95
Designed with excellent Color Rendering Index performance for greater color contrast and visibility.



SEE-THROUGH CHIN PROTECTION
Equipped with transparent chin protection for enhanced range of worksite visibility.



COMPATIBLE WITH GLASSES
Designed for use over corrective glasses.



PANORAMIC LENS
Wide view lens for optimal protection and visibility.



STABLE CARRIER
Provided with carrier for use with helmet.

MARKINGS

CODE **MARKING**

WVI00017- 1000 V | | 2C - 2 | KASK | 1 | B | 8 | 2 | 2 | ATPV 26 cal/cm²

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

3 **10**
YEARS GUARANTEE YEARS SHELF LIFE

SHELF LIFE

10 years starting from the date of manufacture. Shelf life depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

CLEANING

Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor. Do not rub the lens when dry.

ARC FLASH VISOR COLLECTION



WVI00016
ARC FLASH BASIS



WVI00017
ARC FLASH POWER

DISCOVER MORE



SCAN FOR
COMPLETE
COLLECTION