клјк

ΕN

PERFORMANCE WITH A MULTIPLIER EFFECT.

ZENITH X COMBO C



STANDARD EN 397 | 440V a.c. / -30°C / LD / MM EN 50365 (Class 0)

CE 2008 24 8503

EN 12492

for the following clauses only: Shock energy absorption capacity 4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact 4.2.2 | Penetration







WEIGHT 490 g (helmet)

MATERIAL

EXTERNAL SHELL:

HD Polypropylene

INTERNAL SHELL:

Neopor® Ccycled® by BASF | EPS obtained from chemical recycling of



Universal-adjustable from 52 to 63 cm

KASIC

TECHNOLOGIES

CATEGORY

- > D-CORE TECHNOLOGY Low density inner core protects from top impacts.
- > HD CROWN PROTECTION High-density inner shell protection designed for all-around impacts.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- > DRY+ LINER Moisture-wicking fabric for enhanced comfort.
- > ADAPTIVE FIT SYSTEM Size adjustment system that adapts to create a personalized, secure fit.
- > ADVANCED CHINSTRAP 5 adjustment points and EN color-coded fastener.
- > COLOR-CODED FASTENER The color of the fastener indicates the EN standard to which the chinstrap refers.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- > HI-VIZ DETAILS High visibility color shell, luminescent lamp clips and reflective adhesives.





KASK S.p.A. / Via Firenze, 5 - 24060 Chiuduno (BG) - Italy T. +39 035 4427497 / F. +39 035 4427704 / info@kask.com

f 🗿 🖻 (in) kask-safety.c

PRODUCT OF ITAL



