

PROTECTING THOSE WHO  
**HARNESS THE POWER**  
 TO KEEP THE LIGHTS ON  
 AND CITIES RUNNING.

## ZENITH X2 FR ANSI



### STANDARD

ANSI Z89.1 Type I, Type II - Class E  
 All around protection against impact  
 and penetration including front, rear,  
 and sides.

### EN 12492

for the following clauses only:  
 Shock energy absorption capacity  
 4.2.1.2 front impact, 4.2.1.3 lateral  
 impact, 4.2.1.4 rear impact  
 4.2.2 | Penetration  
 4.2.3 | Retention system strenght  
 4.2.4 | Retention system effectiveness



### MATERIAL

EXTERNAL SHELL:  
 HD Polypropylene

INTERNAL SHELL:  
 Self-Extinguish HD Expanded Polystyrene

HEADBAND:  
 Acrylic Webbing



### TEMPERATURE OF USE

-22°F / +122°F | -30°C / + 50°C



### WEIGHT

1.04 lbs | 470 g



### SIZE

One size fits most



WHE00102

○ 201 | ● 221

## TECHNOLOGIES

- FIRE RETARDANT D-CORE & HD CROWN PROTECTION** Protective foam interior treated to self-extinguish.
- FIRE RETARDANT LAMP CLIPS** Replaceable lamp clips treated to self-extinguish.
- FIRE RETARDANT HD POLYPROPYLENE** Offers greater impact energy absorption. Harden surface resists wear and tear.
- FIRE RESISTANT INNER PADDING** High comfort padding resistant to catching fire and is self-extinguishing.
- FIRE RESISTANT CHINSTRAP** Low flammability, non-melting, self-extinguishing chinstrap.
- CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- ADAPTIVE FIT SYSTEM** Size adjustment system that adapts to create a personalized, secure fit.
- EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- ADVANCED CHINSTRAP** 5 adjustment points and EN color-coded fastener.

3

YEARS  
 GUARANTEE

10

YEARS  
 LIFE SPAN



SCAN FOR  
 COMPLETE  
 COLLECTION