\\\\\/100039



Fire-resistant, scratch-resistant, and anti-fog polycarbonate eye protection. Requires KASK Easy Click Adapters FR. Can be worn with corrective glasses. Compatible with KASK Zenith X (Zenith X MAX included), Primero and Quantum helmet series.

The ZEN PLUS VISOR mounted on the QUANTUM helmet, via the EASY CLICK ADAPTERS FR, makes the helmet usable for use in wildland firefighting (EN16471) and technical rescue activities (EN16473) where there is potential exposure to flames.

MOUNTING PARTS







KIT AVAILABLE: WKI00022 VISOR + ADAPTERS

TECHNICAL DETAILS



STANDARD EN ISO 16321 EN 14458

C € 2754

ANSI Z87.1



CATEGORY



MATERIAL Polycarbonate



WEIGHT 80 g



LENGTH 110 mm

TECHNOLOGIES



PANORAMIC LENS

Developed to maximize visibility with minimal viewing distortion.



ENHANCED OPTICAL PERFORMANCE

COMPATIBLE WITH GLASSES

Designed for use with corrective glasses.



ANTI-FOG

Equipped with an anti-fog treatment to increase wearer visibility in a variety of conditions.



DRIP PROOF UPPER CONTOUR

Rubber edge protects eyes from liquid and debris from entering the visor.



ABRASION AND SCRATCH RESISTANCE

Lens treatment designed with protection from abrasion and scratches, increased durability and viewing clarity.



EASY CLICK VISOR ADAPTERS

Requires Easy Click Visor Adaptors to attach to helmet.



CUT PROOF EDGE

Eye shield edge detail designed with a cut proof edge for enhanced wearer safety.

CE MARKINGS

CODE	COLOR	MARKING
WVI00039-500	CLEAR	C € 2754 EN14458:2018 KA/K ZEN PLUS MM/YY = • BT E1/E3 2C-1,2 -30°C +50°C □
	:	KA/K UL1,2 DT 1 -5°C +55°C K N CH 16321 KA/K DT 1-M -5°C +55°C
WVI00039-510	SMOKE	C € 2754 EN14458:2018 KA/K ZEN PLUS MM/YY =
	:	KA/K GL1 DT 1 -5°C +55°C K N CH 16321 KA/K DT 1-M -5°C +55°C
WVI00039-520	MIDDOD	C € 2754 EN14458:2018 K∧/K ZEN PLUS MM/YY = • BT E1/E3 5-2,5 -30°C +50°C □
		KA/K GL2 DT 1 -5°C + 55°C K N CH 16321 KA/K DT 1-M -5°C +55°C

ANSI MARKINGS

CODE	COLOR	MARKING
WVI00039-500	CLEAR	ANSI Z87 + U6 X D3
WVI00039-510	SMOKE	ANSI Z87 + U6 L1.5 X D3
WVI00039-520	SILVER MIRROR	ANSI Z87 + U6 L2 X D3

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

10 years starting from the date of manufacture. Life span depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

CLEANING

Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor.



10 YEARS



SCAN COMPLETE COLLECTION









