

STANDARD

AS/NZS 1801 Type 1

EN 397 | 440V a.c. / -30°C / LD / MM EN 50365 (Class 0)



EN 12492

for the following clauses only: Shock energy absorption capacity 4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact



Adjustable – from 52 to 63 cm



MATERIAL

EXTERNAL SHELL: HD Polypropylene

INTERNAL SHELL: HD Expanded Polystyrene

HEADBAND: Soft PA Nylon



TEMPERATURE OF USE

-30°C / +50°C



WEIGHT

480 g



WHE00090

221

201 222



TECHNOLOGIES

- D-CORE TECHNOLOGY Low density internal core protects from top impacts.
- > HD CROWN PROTECTION High-density inner shell protection designed for all-around impacts.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **DRY+ LINER** Moisture-wicking fabric for enhanced comfort.
- **ADAPTIVE FIT SYSTEM** Size adjustment system that adapts to create a personalized, secure fit.
- > ADVANCED ECO-LEATHER CHINSTRAP 5 adjustment points and EN color-coded fastener.
- > COLOR-CODED FASTENER The color of the fastener indicates the EN standard to which the chinstrap refers.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- > HI-VIZ DETAILS High visibility color shell, luminescent lamp clips and reflective adhesives.

10 YEARS











