ΚΛ/Κ

THE GLOBAL ICON FOR SAFETY AND PERFORMANCE.

STANDARD ANSI Z89.1 Type I, Class C HT-LT

EN 12492

for the following clauses only: Shock energy absorption capacity

- 4.2.1.2 front impact, 4.2.1.3 lateral impact,
- 4.2.1.4 rear impact
- 4.2.2 | Penetration
- 4.2.3 | Retention system strength
- 4.2.4 | Effectiveness of the retention system



One size fits most

TECHNOLOGIES

- > 2DRY LINER Moisture-wicking fabric technology for all-day comfort.
- > UP & DOWN SYSTEM A size adjustment system that enables a comfort fit.
- > VENTILATION CHANNELS 10 air intakes that enhance breathability and comfort.
- > ANTI-INTRUSION MESH Prevents debris from entering ventilation channels.
- > LATERAL ADJUSTMENT DIVIDER Side adjustment points on chinstrap for secure fit.
- > DETACHABLE INNER PADDING Hook-and-loop-enabled padding for easy removal, replacement, & washing.
- > RING TO HOOK Chinstrap loop that securely attaches helmet to a harness.
- > EARMUFF ADAPTER ATTACHMENT POINTS For adapters to secure earmuffs.
- > VISOR ATTACHMENT POINTS For securing KASK eye protection accessories.
- > INTEGRATED LAMP CLIPS 4 built-in, nylon lamp attachment points.



SUPERPLASMA HD

MATERIAL EXTERNAL SHELL: ABS



INTERNAL SHELL: Neopor® Ccycled® by BASF | EPS

obtained from chemical recycling of plastic waste.

KAAK

HEADBAND: Soft PA Nylon

TEMPERATURE OF USE -22°F / +140°F







2025 KASK S.p.A. All



ASSEMBLED IN USA