

## PERFORMANCE WITH A MULTIPLIER EFFECT.

# ZENITH X HI VIZ CE



### STANDARD

EN 397 | 440V a.c. / -30°C / LD / MM  
EN 50365 (Class 0)

CE 2008

EN 12492

for the following clauses only:  
Shock energy absorption capacity  
4.2.1.2 front impact, 4.2.1.3 lateral  
impact, 4.2.1.4 rear impact  
4.2.2 | Penetration



### CATEGORY

III



### MATERIAL

EXTERNAL SHELL:  
HD Polypropylene



### INTERNAL SHELL:

**Neopor® Cycled®** by BASF | EPS  
obtained from chemical recycling of  
plastic waste.

HEADBAND:  
Soft PA Nylon



### TEMPERATURE OF USE

-30°C / +50°C



### WEIGHT

490 g



### SIZE

Adjustable – from 52 to 63 cm



WHE00074

○ 201 | ● 221 | ● 222

## TECHNOLOGIES

- **D-CORE TECHNOLOGY** Low density inner core protects from top impacts.
- **HD CROWN PROTECTION** High-density inner shell protection designed for all-around impacts.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **DRY+ LINER** Moisture-wicking fabric for enhanced comfort.
- **ADAPTIVE FIT SYSTEM** Size adjustment system that adapts to create a personalized, secure fit.
- **ADVANCED CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- **COLOR-CODED FASTENER** The color of the fastener indicates the EN standard to which the chinstrap refers.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- **HI-VIZ DETAILS** High visibility color shell, luminescent lamp clips and reflective adhesives.

3  
YEARS  
GUARANTEE

10  
YEARS  
LIFE SPAN



SCAN FOR  
COMPLETE  
COLLECTION