

#### **STANDARD**

EN 397 | -30°C / LD / MM



## EN 12492

for the following clauses only: Shock energy absorption capacity 4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact 4.2.2 | Penetration 4.1.4 | Ventilation





## **MATERIAL**

**EXTERNAL SHELL:** HD Polypropylene



## INTERNAL SHELL:

Neopor® Ccycled® by BASF | EPS obtained from chemical recycling of plastic waste.

**HEADBAND**: Soft PA Nylon



## **TEMPERATURE OF USE**

-30°C / +50°C



## **WEIGHT**

570 g



Adjustable – from 60 to 66 cm



WHE00132

201	205	210
202	206	214
203	208	215
204	209	

# **TECHNOLOGIES**

- D-CORE TECHNOLOGY Low-density Neopor® Ccycled® EPS core protects from top impacts.
- > HD CROWN PROTECTION High-density Neopor® Ccycled® EPS inner shell protection designed for all-around impacts.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **DRY+ LINER** Moisture-wicking fabric for enhanced comfort.
- **ADAPTIVE FIT SYSTEM** Size adjustment system that adapts to create a personalized, secure fit.
- **VENTILATION CHANNELS** 8 air intakes that enhance breathability and comfort.
- **ADVANCED CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- > COLOR-CODED FASTENER The color of the fastener indicates the EN standard to which the chinstrap refers.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.

10 YEARS



SCAN COLLECTION









