



# **STANDARD**

ANSI Z89.1 Type I Type II, Class C HT-LT All around protection against impact and penetration including front, rear, and sides.

## EN 12492

for the following clauses only: Shock energy absorption capacity 4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact 4.2.2 | Penetration

4.2.3 | Retention system strength

4.2.4 | Effectiveness of the retention system



Adjustable – from 60 to 66 cm



#### **MATERIAL**

**EXTERNAL SHELL:** HD Polypropylene



# **INTERNAL SHELL:**

Neopor® Ccycled® by BASF | EPS obtained from chemical recycling of plastic waste.

**HEADBAND**: Soft PA Nylon



# **TEMPERATURE OF USE**

-22°F / +140°F




## **WEIGHT**

1.19 lb



WHE00136



# **TECHNOLOGIES**

- > D-CORE & HD-CROWN TECHNOLOGY Neopor® Ccycled® internal shell that protects from all-around impacts.
- > ADAPTIVE FIT SYSTEM Size adjustment system that adapts to create a personalized, secure fit.
- > VENTILATION CHANNELS 8 air intakes that enhance breathability and comfort.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- > DRY+ LINER Moisture-wicking fabric for enhanced comfort.
- **LATERAL ADJUSTMENT DIVIDER** Side adjustment points on chinstrap for secure fit.
- **ADVANCED ECO-LEATHER CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- **EARMUFF ADAPTER ATTACHMENT POINTS** For adapters to secure earmuffs.
- > RING TO HOOK Chinstrap loop that securely attaches helmet to a harness.
- > REPLACEABLE LAMP CLIPS 4 lamp attachment clips designed to be removable.

YEARS GUARANTER

YEARS

208 215









