

WVI00035



Full face protection that enables the wearer to work on or be in the vicinity of live electric parts with Class 2 arc flash protection (GS-ET-29), up to 27.0 cal/cm<sup>2</sup> (ASTM F2178-12). Recommended for use with balaclava. Securely flips up and down. Attaches directly to the 30 mm EURO Slots.

Compatible with KASK Zenith X (Zenith X MAX included), Primero and Quantum helmet series.

## TECHNICAL DETAILS



### STANDARD

EN ISO 16321-1  
DGUV GS-ET-29  
ANSI Z87.1 + ASTM F2178  
CSA Z94.3



### CATEGORY

III



### MATERIAL

Polycarbonate



### ATPV

27 cal/cm<sup>2</sup>, ARC 3



### WEIGHT

370 g



### LENGTH

215 mm

### GS-ET-29 (Box-Test)

Class 2 / APC 2

CE 1883 UK CA 0843

## TECHNOLOGIES



### PANORAMIC LENS

Developed to maximize visibility with minimal viewing distortion.



### COMPATIBLE WITH GLASSES

Designed for use over corrective glasses.



### STABLE CARRIER

Reinforced face shield carrier for added protection and durability.



### > CRI 95

Designed with excellent Color Rendering Index performance for greater color contrast and visibility.



### SEE-THROUGH CHIN PROTECTION

Equipped with transparent chin protection for enhanced range of worksite visibility.

## MARKINGS

CODE	COLOR	MARKING
WVI00035	SMOKE	<p><b>KASK</b></p> <p>ATPV27 ERGO</p> <p>MM / YYYY 4 2 2 0 3 1</p> <p>CE 1883 UK CA 0843</p> <p>16321 KASK UL 2 E 6 GS-ET-29 8-2-2 APC 2 ATPV 27 cal/cm<sup>2</sup> ANSI / ISEA Z87.1 KASK Z87+ U6 CSA Z94.3 KASK 2.0</p>

## ADDITIONAL INFORMATION

### GUARANTEE

3 years starting from the date of purchase.

### LIFE SPAN

10 years starting from the date of manufacture. Life span depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

### CLEANING

Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor.

**3**  
YEARS  
GUARANTEE

**10**  
YEARS  
LIFE SPAN



SCAN FOR  
COMPLETE  
COLLECTION