

Flame and fire-resistant, full neck protection designed to protect the wearer from heat and chemicals. Front hook-and-loop closure ensures secure protection of exposed skin and body parts.

Compatible with KASK Zenith X (Zenith X MAX included) and Primero KASK helmet series.

WAC00034-514

MOUNTING



TECHNICAL DETAILS



STANDARD

EN 13688 | Protective clothing - general requirements

EN 11612 | Heat and flame protection

A1 - Limited flame spread

B1 - Convective heat

C1 - Radiant heat

EN 13034 | Protection against chemicals

Type PB [6] - protection against liquid chemicals:

H2SO4 - 30% dilution

NaOH - 10% dilution

o-Xylene – undiluted

Butan-1-ol – undiluted

EN1149-5 | Electrostatic properties (base fabric only)

Half decay time $t_{50} < 4s$

Shielding factor $S > 0.2s$

CE UK CA 0624

TEST

ASTM F1959/05 | IEC 61482/1

ATPV 22.2 cal/cm²



CATEGORY

III



MATERIAL

Double layer fabric in 93% Nomex® 5% Kevlar®, 2% antistatic fiber



WEIGHT

80,5 g



SIZE

One size



FIRE RESISTANT TECHNOLOGIES



FIRE RESISTANT FABRIC

Material: Nomex® | Kevlar®

Test: ASTM F1959-05 | IEC 61482/1 | ATPV 22.2 cal/cm²

Fire-resistant Nomex® fabric. Non-melting, self-extinguishing with no flame.

TECHNOLOGIES



NECK PROTECTION

Designed to protect the neck and ears from the weather and environmental elements.



EASY ATTACHMENT SYSTEM

Integrated helmet slots enable secure attachment of accessories.



PREVENTION

Anti-static base fabric prevents unexpected electrostatic buildup and discharge.



ADJUSTABLE FRONT COVERAGE

Hook-and-loop closure ensures a quick and secure fit.

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

LIFE SPAN

5 years starting from the date of manufacture.

CLEANING

The protection should be washed by hand in cold water or in the washing machine at max 30°C - 85°F.

PRODUCT OF ITALY

3
YEARS
GUARANTEE

5
YEARS
LIFE SPAN



SCAN FOR
COMPLETE
COLLECTION