

WHP00006

EN



Orange-colored earmuffs used in environments with high noise levels. Typical applications include airports, car racing, while using pneumatic drills, etc.

Attaches directly to all Zenith X / Zenith X2 / Zenith X Max / Zenith X2 Max, Primero and Quantum Series helmets and requires Earmuffs Adapters for Superplasma Series helmet.

Compatible with all KASK helmets.

TECHNICAL DETAILS



STANDARD

EN 352-3

CE 1974

ANSI S3.19

CSA Z94.2-02



WEIGHT

350 g



MATERIAL

EAR CUPS AND SPACER:
ABS thermoplastic



SNR (EN 352-3)

SNR 31 dB (A): Plasma, HP, Quantum, Superplasma, Zenith X / Zenith X2 / Zenith X Max / Zenith X2 Max, Primero.

Frequency attenuation value: H 32 dB - M 30 dB - L 21 dB

SNR 28 dB (A): Zenith

Frequency attenuation value: H 30 dB - M 27 dB - L 20 dB

NRR (ANSI S3.19)

27 dB

CSA

Class A



CATEGORY

III

FOAM LINER:

Polyether

TECHNOLOGIES



STANDARD 30 mm SLOT

Designed to attach in 30 mm Euroslot.



COLOR CODED PERFORMANCE LEVEL

Color coded to indicate noise reduction performance level.



EASY SIZE ADJUSTMENT

Designed to adjust seamlessly for almost any headshape or size.



NON-CONDUCTIVE

Designed to not conduct heat or electricity.



CERTIFIED FOR USE WITH KASK HELMET

Performance tested on all KASK helmets.

MOUNTING



WHP00006
SC3 EARMUFFS

ZENITH X

ZENITH X MAX

PRIMERO



WHP00006
SC3 EARMUFFS

WAC00003
EARMUFFS ADAPTERS

SUPERPLASMA

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

LIFE SPAN

5 years starting from the date of manufacture. Earmuffs, and in particular cushions, may deteriorate with use and should be examined at frequent intervals for cracking and leakage. Hygiene Kit should be changed at least twice per year.

CLEANING

Use a damp clean cloth and dry carefully. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the components.

3

YEARS
GUARANTEE

5

YEARS
LIFE SPAN



SCAN FOR
COMPLETE
COLLECTION