



Technical Details

EXTERNAL SHELL: ABS
 INTERNAL SHELL: HD Polystyrene
 HEADBAND: Soft PA Nylon
 SIZE: Universal-adjustable from 53 to 63 cm / 6 ^{5/8} - 7 ^{7/8}
 STANDARD: ANSI Z89.1-2014
 CSA Z94.1-2015 requirements (with the exception of clause 6.3 – protection area)
 EN12492:2012 - Shock energy Absorption Capacity Clauses 4.2.1.2 (front), 4.2.1.3 (lateral), 4.2.1.4 (rear)
 Retention system strength clause 4.2.3,
 Effectiveness of the retention system clause 4.2.4
 TYPE 1 CLASS E



430 g / 0.92 lb



ANSI: -20°C / +50°C
 -4°F / +122°F



WHE00044.201
 WHITE
 also in XL FR fit
 WHE00060.201

Technology



PROTECTION AGAINST ELECTRIC SHOCK: Helmet provides protection against electrical hazards for use in the vicinity of low voltage systems with voltages up to 20.000 V.



CHINSTRAP FR: Highly heat resistant chinstrap made of Nomex. Withstands temperatures of up to 360 °C for short periods. Does not melt. Selfextinguishing with no flame. Low flammability. Good chemical resistance against low-strength acids and alkalines.



LAMP CLIPS: Helmet is equipped with strong removable carrying clips, compatible with all headlamps with elastic bands on the market.



RING TO HOOK: Fitted with a special hook on the chinstrap which allows the helmet to be connected to the harness.



FAST 3DRY: High-tech 3D fabric that dries very quickly, helping the dispersion of moisture to the outside and leaving a pleasant feeling.



UP & DOWN 2.0: The innovative and exclusive UP & Down 2.0 technology ensures a precise and comfortable fit around the back of the head. The center wheel and the two side wings allow the quick adjustment of the helmet not only in width but also in height and tilt.



REMOVABLE FRONT PAD: Front-end padding easily removable and washable. Developed to guarantee maximum breathability and optimum moisture absorption. Designed to adhere to the front, optimizing comfort.



VISOR ATTACHMENT: Provided with visor attachments slots.



EARMUFFS FITTING: Built with integrated slot for earmuffs. Compatible with KASK earmuffs.

Up & Down 2.0 size adjustment

Up & Down 2.0 size adjustment system guarantees improved fitting thanks to the updated design. Higher precision and comfort are provided by the freedom of movement of the lateral arms of the system. The mechanism consists of a central ratchet wheel that allows to dial in the tension and two lateral winglets for rapid and exact tuning of the size. This advanced size adjustment system offers high stability of the helmet due to two additional adjustments of height and inclination, allowing correct positioning and ultimate fit of the helmet.



Additional Information



WARRANTY

3 years starting from the purchasing date.

SHELF LIFE

10 years starting from the production date (production date is printed on the label inside the helmet).

Inspect the helmet regularly to check for any damage! Cuts, abrasions, deformation or changes in colour represent important elements for checking the helmet status.

CLEANING

Clean the helmet only with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). Do not use chemical detergent or solvent.

STORAGE

When not in use the helmet should be stored away from direct sunlight or source of heat.

Accessories



WVI00007
ZEN VISOR



WVI00009/10
ZEN MESH VISOR



WVI00008
ZEN FF VISOR



WVI00016
ARC FLASH BASIC



WVI00017
ARC FLASH POWER



WAC00009
VISOR ADAPTOR



WAC00010
VISOR CARRIER



WVI00011
PEAK



WPA00006
REPLACEMENT
INNER PADDING



WAC00013
NECK SHADE



WAC00025
NECK SHADE HI VIZ



WHP00004/5/6
EARMUFFS



WPA00007
WINTER PADDING



WAC00026
HELMET BAG